Flint Aero, Inc 1942 Joe Crosson Drive El Cajon, CA 92020

SUPPLEMENTAL AFM NUMBER: 210 STC Number: SA1527WE

FAA APPROVED SUPPLEMENTAL AIRPLANCE FLIGHT MANUAL

TO

CESSNA MODELS:

210, 210A, 210B, 210C, 210-5, 210-5A

This FAA approved Supplemental Airplane Flight Manual must be available to the pilot when the airplane is modified by the installation of Flint Aero auxiliary fuel system with transfer pumps in accordance with STC SA1527WE.

The information contained herein supplements or supersedes the basic placards and marking on in those areas listed herein. For limitations, procedures, and performance information not contained in this manual, consult the basic placards and markings.

LIMITATIONS: Placard on instrument panel in view of the pilot: Ι. "Total aux fuel 24 U.S. gals. (23 gal. useable) Transfer aux fuel only in level flight when main is half empty and when main tank is not supplying engine. Aux fuel switch must be off during take off, landing, refueling, and when empty. For utility category, aux tank fuel switch must be off and aux tanks must be empty."

II. PROCEDURES: No Change

III. PERFORMANCE: No Change.

FAA APPROVED:

Manager, Flight Test Branch, ANM-160L Los Angeles Africaft Certification Office

Transport Airplane Directorate

Date: January 7, 2013

Revision: A

Revision IR approved September 16, 1988